

## FAGOR INDUSTRIAL

## FEATURES PER RANGE

MACHINE TYPE		HOOD-TYPE			FRONT LOADING			GLASS- WASHERS
RANGE		ADVANCE	CONCEPT+	CONCEPT	ADVANCE	CONCEPT+	CONCEPT	CONCEPT
EFFI WASH	EFFI-WASH Newly optimized hydraulic system provides a strong mechanical action combined with the optimum clean water in the tank, and the balanced power to keep the perfect hygienic temperature during the whole lifetime of the machine.	•	•	•	•	•	•	•
EFFI RINSE	EFFI-RINSE EFFI-RINSE system assures a perfect hygienic result with a linear 85°C full rinsing cycle thanks to its incorporated rinsing pump and air break system design.	•	•	-	•	•	-	-
EFFI SILENT	EFFI-SILENT Full Double skin body to isolate machine's noise from the environment, making the atmosphere more peaceful.	•	-	-	•	•	•	-
HRS	HRS Fagor's HRS collects and condenses the steam exhausted by the machine after a full cleaning cycle, and heats up the input water from 10°C to 25°C (for example). It also allows to avoid installing a hood in most of the cases.	0	0	0	-	-	-	-
MULTI POWER	MULTIPOWER Several machines in one. Perfect solution to minimize your stock. By making an easy change in the electrical connecting box during the installation, you will be able to have a 3.4 kW machine or 6.2 kW or other powers.	•	•	•	•	•	• Except CO-5	-
SELF DRAIN	SELF-DRAIN  Every washing cycle, SELF-DRAIN takes care of removing dirty water from the tank just before starting to fall the rinsing clean and hot water over the ware.	•	-	-	•	-	-	-
SCI FILTER	SCI FILTER  Consists in a simple 3 steps filtering system for big, medium and small size dirtiness particles; allowing to keep the wash tank water clean for a longer period of time.	•	-	-	•	-	-	-
SOFT START	SOFT-START It assures a low noise level of the bar or restaurant where it is installed and prevents the glasses and ware from moving inside the basket, protecting them from breaking and improving the washing cycle of all the ware.	-	-	-	•	•	•	-
FAGOR SERVICE	FAGOR SERVICE Access to internal menu through password to display and check the status of all components: pumps, switches, heating elements, temperature and pressure sensors, etc.	•	-	-	•	-	-	-
SCIENCE	SCIENCE ONE TOUCH AT A GLANCE elevates its simplicity and smartness to one single Multi-chromatic button, making operator's life easier and optimizing the operating costs thanks to its intuitive 3 colors code.	•	-	-	•	-	-	-
FILL	ECO FILL The NEW Thermostatic tank water filling system: allows to speed up drastically the start-up time of the machine, because the wash tank is filled in with hot water previously heat in the boiler.	•	•	-	•	•	-	-
GN-1/1	GN-1/1 Using our special basket CB7-GN, E-VO Concept, Concept+ and Advance undercounters and hood-type machines are able to wash perfectly GN 1/1 trays. A huge advantage for our customers, thanks to its 380 mm clearance for undercounters and 440 mm for hood-types. A real proof of versatility.	•	•	•	•	•	•	-
ROCK COUNTER- BALANCED	ROCK COUNTERBALANCED DOOR Double spring and stainless steel hinge system tested to resist the strongest usage of the market, with more than 360.000 openings.	-	-	-	•	•	•	-
KITS PHILOSOPHY	KITS PHILOSOPHY Reduce stock and simplify your order by just selecting the basic versions and adding the kits when required: detergent dispenser and drain pump.No need to have many versions in your stock. Easy to install kits with easy accessibility to the components minimizing the installation risks.	•	•	•	•	•	•	•
PHILOSOPHY	STAMPED PHILOSOPHY A fully new stainless steel body and structure made to resist and resist to the strongest usage of the market.	•	•	•	•	•	•	-
ZERO	IPx5 ZERO-HUMIDITY Designed to have a full protection IPx5 against water hose cleaning and external humidity.	•	-	-	•	-	-	-
SELF CLEANING	SELF-CLEANING It allows the user to avoid hand-cleaning, because the machine will make it for you with this function. It will wash the chamber with detergent, rinse it all and drain everything away, leaving the machine without water in the tank and boiler. This will prevent bad smell and increase your machine's lifetime.	•	-	-	•	-	-	-
MULTI VOLTAGE	MULTIVOLTAGE (1+N/3+N)	•	•	•	•	•	• Except CO-5	<b>-</b> 00
THERMO STOP	THERMOSTOP (83 °C)	•	•	Factory disabled	•	•	Factory disabled	Only CO-402

<sup>•</sup> Standard O Option - Not version



