



## - Available options for Standard Press upon request:

**EURO** 

	U	UL	UP	UPL	Р	PL	
1 9-It automatic electric boiler with electronic control, 10- or 12-kW heating							
elements, <b>4.8-bar</b> working pressure and pump.  Volt. 400-3+N-50 Hz.	•	•	•	•	•	•	1.595
2 <b>20-lt</b> automatic electric boiler with electronic control, <b>10-</b> or <b>12-kW</b> heating							
elements, <b>4.8-bar</b> working pressure and pump.							
Volt. 400-3+N-50 Hz.	•	•	•	•	•	•	2.402
3 15- or 18-kW heating elements (only with option #2).	•	•	•	•	•	•	237
4 9+6-kW - 9+7.5-kW - 9+9-kW twin indipendent elements (only with option							
#2).	•	•	•	•	•	•	465
5 Vacuum motor. Volt. 230-1- 50 Hz.	•	•	•	•	•	•	558
6 Extra charge for inverted vacuum/steam pedals.	•	•	•	•	•	•	65
7 Steam spotting gun.	•	•	•	•	•	•	154
8 Steam/air spotting gun. (Compressed air required).	•	•	•	•	•	•	261
9 Vacuum arm with spotting shape F6.	•	•	•	•	•	•	376
10 Vacuum arm with sleeve shape F3 and foot-pedal.	•	•	•	•	•	•	486
11 Vacuum arm with heated sleeve shape F3/R and foot-pedal.	•	•	•	•	•	•	579
12 Water spray gun with condenser and holder.		•		•		•	338
13 GFV steam iron assembly with electric steam iron, pivoting iron rest and							
steam hoses.	•	•	•	•	•	•	683
14 "ALL STEAM" iron assembly, with: pivoting iron rest, steam hoses and							
thermodynamic steam trap.		•	•	•	•	•	889
15 Anti-gloss teflon-coated head for utility shape.	•						713
16 Anti-gloss teflon-coated head for utility/legger shape.			•				772
17 Anti-gloss teflon-coated head for legger shape.					•		859
18 Anti-gloss NOMEX cover for POLISHED hot head.		•		•		•	77
19 Garment-tray extension for either sides.	•	•	•	•	•	•	84