

**- Available options upon request for Brava Press:**

	U	UL	B	EURO
1 <b>9-It</b> automatic electric boiler with electronic control, <b>10-</b> or <b>12-kW</b> heating elements, <b>4.8-bar</b> working pressure and pump. Volt. 400-3+N-50 Hz.	•		•	<b>1.595</b>
2 <b>20-It</b> automatic electric boiler with electronic control, <b>10-</b> or <b>12-kW</b> heating elements, <b>4.8-bar</b> working pressure and pump. Volt. 400-3+N-50 Hz.	•		•	<b>2.402</b>
3 <b>9-It</b> automatic electric boiler with electronic control, <b>10-</b> or <b>12-kW</b> heating elements, <b>4.8-bar</b> working pressure, including: pump and device for automatic <b>HEATING</b> of the bucks. Volt. 400-3+N-50 Hz.		•		<b>1.785</b>
4 <b>20-It</b> automatic electric boiler with electronic control, <b>10-</b> or <b>12-kW</b> heating elements, <b>4.8-bar</b> working pressure, including: pump and device for automatic <b>HEATING</b> of the bucks. Volt. 400-3+N-50 Hz.		•		<b>2.610</b>
5 15- or 18-kW heating elements (only with options #2 or #4).	•	•	•	<b>237</b>
6 9+6-kW, 9+7.5-kW, 9+9-kW twin independent elements (only with options #2 or #4).	•	•	•	<b>465</b>
7 Vacuum motor. Volt. 230-1-50 Hz. (as an alternative to option #8).	•	•	•	<b>558</b>
8 Vacuum/BLOWING motor. Volt. 230-1-50 Hz. (as an alternative to option #7).	•	•		<b>1.364</b>
9 1-HP built-in air compressor. Volt. 400-3+N-50 Hz.	•	•	•	<b>1.077</b>
10 Steam spotting gun.	•	•		<b>154</b>
11 Steam/air spotting gun.	•	•		<b>261</b>
12 Vacuum arm with spotting shape F6.	•	•		<b>376</b>
13 Vacuum arm with sleeve shape F3.	•	•		<b>486</b>
14 Vacuum arm with heated sleeve shape F3/R.	•	•		<b>579</b>
15 Water spray gun with condenser and holder.		•		<b>338</b>
16 GFV steam iron assembly with electric steam iron, pivoting iron rest and steam hoses. Volt. 230-1-50 Hz.	•	•		<b>683</b>
17 "ALL STEAM" iron assembly, with: pivoting iron rest, steam hoses and thermodynamic steam trap.	•	•		<b>889</b>
18 GFV steam iron assembly with steam electric iron, pivoting iron rest, steam hoses and <b>SAFETY device</b> (mandatory for 1-button closing). Volt. 230-1-50 Hz.	•	•	•	<b>752</b>
19 "ALL STEAM" iron assembly, with: pivoting iron rest, steam hoses, thermodynamic steam trap and <b>SAFETY device</b> (mandatory for 1-button closing+1).	•	•	•	<b>958</b>
20 Adjustable head-release timer.		•		<b>322</b>
21 Anti-gloss teflon-coated head for utility shape.	•			<b>713</b>
22 Anti-gloss NOMEX cover for POLISHED hot head.		•		<b>77</b>
23 Garment-tray extension for either sides.	•	•		<b>84</b>